



SERDI

SW 1200

**Heavy duty pneumatic cylinder head work bench.
For disassembling and assembling of valve springs on cylinder
head of cars, trucks and motorcycles.**

**Valve compressor lock for easy retainer removal (hands free).
Access for camshaft and all other cylinder head operations.**



Handwheel for easy angle adjustment

Pneumatic foot control

5 sizes pressure foot (open design)

Variable speed regulation for air cylinder

Air cylinder easily tilts to any valve angle and assembly slides from valve

Tool and accessories drawers for convenient components storage

Valve keeper installing tool

Valve keeper retrieving tool

Surface covered with 9 mm thick aluminium plate

TECHNICAL FEATURES

Dimensions

Length	mm / inch	1550 / 61
Width	mm / inch	850 / 33.4
Height	mm / inch	1710 / 67.2

Table surface

Length	mm / inch	1300 / 51.1
Width	mm / inch	360 / 14.1

Max cylinder head capacities

Length	mm / inch	1350 / 53.1
Width	mm / inch	460 / 18.1
Height	mm / inch	270 / 10.6

Compression force

4.436 N at 10 bar = 445 Kg = 985 LBS

Shipping dimensions

Length	mm / inch	2000 / 78.7
Width	mm / inch	1200 / 47.2
Height	mm / inch	1930 / 76
Net weight	kg / lbs	300 / 661
Net weight with packing	kg / lbs	455 / 1003

Connections

Pneumatic supply	bar	6-10
------------------	-----	------



Piston movement:
200 mm



-45 to +20° rotating table
adjustment



Four drawers




Pneumatic pedal



MACHINES SERDI S.A.

23, avenue des vieux moulins
B.P. 380
74012 Annecy Cedex
France

 00 33 4 50 65 63 00


Fax: 00 33 4 50 52 99 92

www.serdi.com

Email: export@serdi.com

SERDI CORP.

1526 Litton Drive
Stone mountain
Georgia 30083
USA

 (770) 493 82 20

Fax: (770) 493 83 23

Your distributor: